

Item no.: 734-110
Product description: FEMALE CONNECTOR 10 POLE PIN SPACING 3.5 MM / 0.138 IN 100% PROTECTED AGAINST MISMATING WITH CODING FINGERS



Produkt kann von Bild abweichen / product may differ

Packing unit 50 pieces

Product group	3 (Multi Conn. System)
Weight	7.6 g
Color	light gray
No. of connection Points	10
No. of potentials	10
pole count	10
Height	13.4 mm
Height	0.528 in
Width	37.2 mm
Width	1.465 in
Depth	18.6 mm
Depth	0.732 in
Pin spacing from	3.5 mm
Pin spacing from	0.138 in
Pollution degree	2
Measured voltage EN	160 V
Measured shock voltage	2.5 kV
Current intensity EN	10 A
Pollution degree	2

Measured voltage EN	320 V
Measured shock voltage	2.5 kV
Current intensity EN	10 A



Connection method	CAGE CLAMP® CONNECTION
Cross section [mm ²]	0.08 - 1.5 mm ²
Wiring method	solid
Cross section [mm ²]	0.08 - 1.5 mm ²
Cross section [mm ²]	0.25 - 1.5 mm ²
Cross section [mm ²]	0.25 - 1.5 mm ²
Cross section [AWG]	28 - 14 AWG
Strip length from	6 mm
Strip length to	7 mm
Material group	I
xxx-xxx/034-000	Strain relief plate 25 mm



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
734-110	ABS	04-HG469925/1-PDA	250	10	0,5-1,5
734-110	BV	11915/A0	250	10	0,5-1,5
734-110	CSA	154112-1465035	300	10	28-14
734-110	DNV	E-9218	250	10	0,5-1,5
734-110	GL	17296-00HH	250	10	0,5-1,5
734-110	KEMA	2077592.02	250	10	0,5-1,5
734-110	LR	96/20035	250	10	0,5-1,5
734-110	RMR	11130002	250	10	0,5-1,5
734-110	UR	E45171	250	10	28-14
734-110	UR	E45172	300	10/10	28-14

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected