# **TRM** Time-Delay Midget Fuses

Tri-Onic<sup>®</sup> TRM time-delay midget fuses are rated 250 volts AC and are offered in ampere ratings from 1/10 to 30A. They have 12 seconds time-delay at 200% rating to provide supplemental protection of small motors, small transformers and other high inrush loads, plus many other 250 volt applications. (Not for Branch Circuit Protection).

## Features/Benefits:

- Numerous ratings for a wide variety of applications
- 250VAC rating in all sizes up to 30A
- Time-delay for circuits with high inrush currrent
- Can be used with UltraSafe<sup>™</sup> fuse holders
- 1 1/2" x 13/32" (10mm x 38mm) dimensions

## Highlights:

• Time-delay

## **Applications:**

- Small motors
- Small transformers
- Lighting circuits
- Control circuits

## **Catalog Numbers (amps)**

TRM1/10	TRM6/10	TRM1-6/10	TRM3	TRM5-6/10	TRM10
TRM15/100	TRM8/10	TRM1-8/10	TRM3-2/10	TRM6	TRM12
TRM2/10	TRM1	TRM2	TRM3-1/2	TRM6-1/4	TRM15
TRM1/4	TRM1-1/8	TRM2-1/4	TRM4	TRM7	TRM20
TRM3/10	TRM1-1/4	TRM2-1/2	TRM4-1/2	TRM8	TRM25
TRM4/10	TRM1-4/10	TRM2-8/10	TRM5	TRM9	TRM30
TRM1/2					

## Recommended Fuse Blocks for Midget (10x38mm) Fuses

	Catalog Number				
Number of Poles	UltraSafe™ Indicating Fuse Holder	Screw Connector	Pressure Plate Connector	Copper Box Connector	
Adder		30310	30320	30350	
1	USM1I	30311	30321	30351	
2	USM2I	30312	30322	30352	
3	USM3I	30313	30323	30353	
3	USFM10I				



## **Ratings:**

Volts	: 250VAC
Amps	: 1/10 to 30A
I.R.	: 10kA I.R.

## Approvals:

- UL listed to standard 248-14 File E33925
- CSA Certified to Standard C22.2 No. 248.14



