


Item no.: 734-170
 Product description: HEADER RIGHT ANGLE SOLDER PIN, 1 X 1 MM / 0.039 X 0.039 IN 10 POLE PIN SPACING 3.5 MM / 0.138 IN 100% PROTECTED AGAINST MISMATING WITH CLOSED END MATING DIRECTION PARALLEL TO PCB



Produkt kann von Bild abweichen / product may differ

Packing unit 100 pieces

RoHS compliant

Product group	3 (Multi Conn. System)
Weight	2.68 g
Color	light gray
pole count	10
Height	8.5 mm
Height	0.335 in
Width	37.4 mm
Width	1.472 in
Depth	10.3 mm
Depth	0.406 in
Pin spacing from	3.5 mm
Pin spacing from	0.138 in
Pollution degree	2
Measured voltage EN	160 V
Measured shock voltage	2.5 kV
Current intensity EN	10 A
Pollution degree	2

Measured voltage EN	320 V
Measured shock voltage	2.5 kV
Current intensity EN	10 A
Material group	I
Contact material	Electrolytic copper (Ecu)
Contact surface	tin-plated



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
734-170	ABS	04-HG469925/1-PDA	250	10	0,5-1,5
734-170	BV	11915/A0	250	10	0,5-1,5
734-170	CCA	NL5641	250	10	0,5-1,5
734-170	CSA	154112-1465035	300	10	28-14
734-170	DNV	E-9218	250	10	0,5-1,5
734-170	GL	17296-00HH	250	10	0,5-1,5
734-170	KEMA	2077592.02	250	10	0,5-1,5
734-170	LR	96/20035	250	10	0,5-1,5
734-170	RMR	11130002	250	10	0,5-1,5
734-170	UR	E45171	250	10	28-14
734-170	UR	E45172	300	10	

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected