

# IEC Female Power Connectors

**F5581** = Product group; Product group discount F 55 8\_

## K+B IEC Female Power Connectors

Pin Temperature: 65°C  
Series: GSD, GTK

Part Nr.	Part description
GSD4-4.8	IEC Power Jack, Spacing=40mm 4,8mm
GSD4-6.3	IEC Power Jack, Spacing=40mm 6,3mm
GSD4SI	IEC Power Jack, Snap-In
GSD4SI-6.3	IEC Power Jack, Snap-In, 6,3mm
GTK0-2A	IEC Combi, 2xJack, Snap-In

### Technical Specifications

Nr. of Poles: .....2+PE  
Continuous Current: .....10A (UL,CSA:15A)  
Pin Temperature: .....65°C  
Rated Voltage: .....250V AC

### GSD4-\_\_

#### Features

- Appliance socket, longitudinal flange, distance between fixing holes 40mm
  - Screw terminals
- GSD4-4.8: 4,8mm  
GSD4-6.3: 6,3mm

#### Approvals



### GSD4SI, GSD4SI-6.3

#### Features

- Appliance socket, snap-in assembly
  - Connection by
- GSD4SI: solder lug terminals  
GSD4SI-6.3: 6,3mm flat cable plug

#### Approvals



### GTK0-2A

#### Features

- Combination of two appliance sockets
- Solder-lug terminals
- Snap-in panel

#### Dimensions

Type	L±0,2 [mm]	F±0,2 [mm]
GTK0-2A	51	48,3

#### Approvals



#### Note

- You will find suitable flat receptacles for tabs 4,8mm in product group F1313.
- You will find suitable flat receptacles for tabs 6,3mm in product group F1315.

#### Norms

EN60320 T2-2, standard sheet F

#### Terms of Delivery

Minimum order quantity: 1 PKU = 10 pieces

#### Manufacturer:

<http://www.kb-connector.de>

