



Type ITS - MSM	2520-12	2520-24	3222-12	3222-24
A	25	25	32	32
B	20	20	22	22
C	200	200	200	200
D	M4	M4	M4	M4
E	6	6	6	6
G	M3	M3	M3	M3
H	9	9	12	12
Leitungsfarbe	blau	rot	blau	rot
Spannung [VDC]	12	24	12	24
Leistung [W]	3,2	3,2	3,6	3,6
Haftkraft [N]	140	140	240	240
Ankerdicke [mm]	3	3	4	4
Gewicht [kg]	0,06	0,06	0,11	0,11

	Maße in mm Dimensions in millimeters	Zul. Abw. f. Maße ohne Toleranzang. General tolerances	Fertigzustand finished cond.	Maßstab Scale 1:1	Menge Quantity 1
		ISO 2768-Km		Rohstoff/Raw material - Rohteil-Nr./Raw piece No. - Werkzeug-Nr./Tool No. -	
		2014 Datum Date	Name Name	Benennung/Designation	
		Bearb. Drawn 30.09.14	F. Käsbauer	Elektromagnete Edelstahlausführung	
		Gepr. Check 30.09.14	A. Huber		
		Norm Appr.		Sachnummer/Part-No.	
				ITS-MSM- _ _ _ - _ _ _ - VDC-VA	
A	30.09.14	AH		Blatt 1 Sheet 1 von 1 of 1	
Ausg. Issue	Änderung Modification	Datum Date	Name Name	Ursprung Source	