

FTCAP GmbH
 Carl-Benz Str- 1
 25813 Husum / Germany
 Tel. +49 (0) 4841 8957 0
 Fax. +49 (0) 4841 8957 45
 Email info@ftcap.de

FTCAP GmbH

Data sheet



Customer : Schukat Electronic Vertriebs GmbH


Drawing No. :1010527-51816

Seite 1 / 1

created: 29/11/2012 14:37:00

Typ : A47204021036

RoHS Compliant



\varnothing D : 21 mm
 L : 36 mm
 l : 40 mm
 d : 0,8 mm

Terminals : Wire

Electrical Parameters

Rated Capacitance (C_R) @ 100 Hz / 20 °C	4700 μ F	
Tolerance	± 20 %	
Rated Voltage (U_R)	40 V	
Surge Voltage (U_S) max. 5 x 1 min / h	46 V	
Reverse Voltage (U_U) max. 1 s	2 V	
Leakage Current (I_L) @ U_R / 5 min / 20 °C	1510 μ A	
ESR typ. @ 100 Hz / 20°C	92 m Ω	
Tan δ typ. @ 100 Hz / 20°C	27 %	
Z max. @ 10 kHz / 20°C	85 m Ω	
ESL typ.	20 nH	
Rated Ripple Current (I_R) @ 100 Hz / 85°C	1,3 A	
Useful life @ I_R , U_R , 85°C	5000 h	
IEC Climatic category / Standards	40/85/56	IEC 60384-4
Applications	general industrial	
Your article No. / Project		