




<b>fitted with</b>	LED
<b>work equipment</b>	Energy efficiency category A+
<b>connected load</b>	without
<b>power consumption</b>	20-28V; DC
<b>luminous flux</b>	approx. 16 W
<b>luminous efficacy</b>	approx. 1720 lm
<b>light distribution</b>	approx. 108 lm/W
<b>light colour</b>	direct, narrow-angled beam
<b>color rendering index (CRI)</b>	neutral white, approx. 5000 K
<b>system of protection</b>	> 80
<b>class of protection</b>	IP 67
<b>technology</b>	III
<b>usage</b>	switchable
<b>luminaire body</b>	external
<b>lamp cover</b>	aluminium, anodised, aluminium coloured anodised
<b>weight (net)</b>	screen, clear
<b>mains supply</b>	approx. 0.8 kg
<b>design</b>	built-in plug
<b>fastening</b>	RSFM 4/0,05 P25-1
<b>dimension</b>	mounted version
<b>special features</b>	L-angle, clamp
	A=540 mm
	angle of illumination 40°



RSFM 4/0,05 P25-1

**illuminance**

distance: 100 cm  
**Em:** 746 lx  
**Emax:** 1270 lx  
**Emin:** 285 lx



**luminous intensity**

