





**Features :**

- adopt super bright SMD LEDs as the light source
- wide range of application: interior design, furniture (cabinets, bookshelf, cupboard), showcase, cove lighting, stairs, advertisement
- profile can fit slim design and thin furniture pieces
- lightweight
- easily release heat
- easy to install
- environment friendly
- quality approved by GovenA

**Aluminium LED profiles with LED stripes**

Photo	Product code	Power [W]	Voltage [V]	Lenght	Color	Cover	End caps PC	Mounting brackets (holder)	Mounting	Material	Surface finishing	Waterproof	International Protection
 Type A	LEDPR-A36-3528C-60	1,4 W	DC 12 V	0,36 m	White	frosted	2pcs	no	in narrow space	Standard AA6063	anodized	no	IP20
	LEDPR-A36-3528W-60	1,4 W	DC 12 V	0,36 m	Warm white	frosted	2pcs	no	in narrow space	Standard AA6063	anodized	no	IP20
	LEDPR-A46-3528C-60	1,9 W	DC 12 V	0,46 m	White	frosted	2pcs	no	in narrow space	Standard AA6063	anodized	no	IP20
	LEDPR-A46-3528W-60	1,9 W	DC 12 V	0,46 m	Warm white	frosted	2pcs	no	in narrow space	Standard AA6063	anodized	no	IP20
	LEDPR-A56-3528C-60	2,4 W	DC 12 V	0,56 m	White	frosted	2pcs	no	in narrow space	Standard AA6063	anodized	no	IP20
	LEDPR-A56-3528W-60	2,4 W	DC 12 V	0,56 m	Warm white	frosted	2pcs	no	in narrow space	Standard AA6063	anodized	no	IP20
	LEDPR-A76-3528C-60	3,4 W	DC 12 V	0,76 m	White	frosted	2pcs	no	in narrow space	Standard AA6063	anodized	no	IP20
	LEDPR-A76-3528W-60	3,4 W	DC 12 V	0,76 m	Warm white	frosted	2pcs	no	in narrow space	Standard AA6063	anodized	no	IP20
 Type C	LEDPR-C36-3528C-60	1,4 W	DC 12 V	0,36 m	White	frosted	2pcs	2pcs	mounting brackets	Standard AA6063	anodized	no	IP20
	LEDPR-C36-3528W-60	1,4 W	DC 12 V	0,36 m	Warm white	frosted	2pcs	2pcs	mounting brackets	Standard AA6063	anodized	no	IP20
	LEDPR-C46-3528C-60	1,9 W	DC 12 V	0,46 m	White	frosted	2pcs	2pcs	mounting brackets	Standard AA6063	anodized	no	IP20
	LEDPR-C46-3528W-60	1,9 W	DC 12 V	0,46 m	Warm white	frosted	2pcs	2pcs	mounting brackets	Standard AA6063	anodized	no	IP20
	LEDPR-C56-3528C-60	2,4 W	DC 12 V	0,56 m	White	frosted	2pcs	2pcs	mounting brackets	Standard AA6063	anodized	no	IP20
	LEDPR-C56-3528W-60	2,4 W	DC 12 V	0,56 m	Warm white	frosted	2pcs	2pcs	mounting brackets	Standard AA6063	anodized	no	IP20
	LEDPR-C76-3528C-60	3,4 W	DC 12 V	0,76 m	White	frosted	2pcs	2pcs	mounting brackets	Standard AA6063	anodized	no	IP20
	LEDPR-C76-3528W-60	3,4 W	DC 12 V	0,76 m	Warm white	frosted	2pcs	2pcs	mounting brackets	Standard AA6063	anodized	no	IP20

Aluminium LED profiles without LED stripes

Photo	Product code	Power [W]	Voltage [V]	Lenght	Color	Cover	End caps PC	Mounting brackets (holder)	Mounting	Material	Surface finishing	Waterproof	International Protection
	PR-A200A	-	-	2,00 m	to chose	frosted	4pcs	no	in narrow space	Standard AA6063	anodized	no	IP20
	PR-C200A	-	-	2,00 m	to chose	frosted	4 pcs	4pcs	mounting brackets	Standard AA6063	anodized	no	IP20

End caps:



Type A



Type C

Mounting brackets

