


**SAFETY ISOLATING TRANSFORMER**

POWER : 14VA  
 INPUT VOLTAGE : 2x115V  
 FREQUENCY : 50/60Hz  
 NOMINAL OUTPUT VOLTAGE : 2x9V

NON SHORT CIRCUIT PROOF TRANSFORMER  
 IP00  
 UL94HB  
 OPERATING TEMPERATURE : -25°C to 50°C  
 STORAGE TEMPERATURE : -25°C to 85°C  
 INSULATION CLASS (IEC85) : B  
 REQUIRED PROTECTION : ON PRIMARY 160mA (115V)  
 80mA (230V)

STANDARDS :  
 UL506 (File E111078)  
 CSA 22-2 (File E111078)  
 CE

CONFORM TO :  
 EN61558-1  
 EN61558-2-6



D					
C					
B					
A					
Rev	Date	Modification	Dessiné	Visa	

Finition:		Tolérance générale:	
Finition:		General tolerance:	
Ech: 1:1	Matière:		
	Material:		
Dessiné par: ROUSSEL.Ch	Date: 20/09/2005	Visa:	J.P.M.
<b>DATA SHEET 45044</b>			
<b>UI 39x10.2</b>			
		22 Allée du Clos des Charmes Z.A. Les Portes de la Forêt 77030 COLLEIGNY Tel : 01-60-37-55-55 Fax : 01-60-17-12-00	
		<b>DS45044</b>	