



Wire sizes

Solid min	0.2 mm ²
Solid max	4.0 mm ²
Stranded (flexible) min	0.2mm ²
Stranded (flexible) max	2.5 mm ²
Stranded with Ferrule min	0.25 mm ²
Stranded with Ferrule max	2.5 mm ²

Dimensions

Stripped Length	8.0 mm
PCB Hole Diameter	1.3 mm

Materials

Clamp	Brass
Screw	Steel
Solder Tab	Copper Alloy

Insulating Material

Material	PA 6.6
Flammability Class	UL 94 V-0

Temperatures

Operating Temperature (without mech. load)	-40 °C - 105 °C
Store Temperature	-40 °C - 105 °C

Wave Soldering Process

Soldering Temperature, recommended	260 °C
Peak Soldering Time, recommended	3-4 s

Reflow Process

Soldering Temperature, recommended	-
Peak Soldering Time, recommended	-

**Technical Data // AKZ700/..-5.08-H-GRÜN**

Spacing 5.08 mm

Colours

GREEN, RAL 6018

GREY, RAL 7016

PEBBLE GREY, RAL 7032

BLUE, RAL 5015

LIGHT GREEN, similar RAL 6018

Colours according to RAL, there may be variations on colour due to production conditions.
Special colours on request.**Ratings**

UseGroup	C _{RU} US			VDE	
	B	C	D	min	max
Rated Voltage	300 V	-	300 V	250 V	
Rated Current	15 A	-	10 A	24 A	
Rated Wire Size				min	max
- solid	AWG 30-12	-	AWG 30-12	0.5 mm ²	4.0 mm ²
- stranded	AWG 30-12	-	AWG 30-12	0.5 mm ²	2.5 mm ²
Torque	0.45 Nm	-	0.45 Nm	0.50 Nm	
Screw Size	M3	-	M3	M3	
Test Voltage	1.60 kV	-	1.60 kV	2.0 kV	

Accessoires

Figure	Designation	Article Number
	Bridge, 2-pole, insulated, BRI/2-5.0/5.08-LIGHT GREY	Order Data: 50000000006
	Bridge, 3-pole, insulated, BRI/3-5.0/5.08-LIGHT GREY	Order Data: 50000000007
	Bridge, 2-pole, BR/2-5.0/5.08-L7.0	Order Data: 50000000008
	Screw Cover SC-AK700-YELLOW	Order Data: 50700000004



Technical Data // **AKZ700/..-5.08-H-GRÜN**

Spacing 5.08 mm

Order Data (Spacing 5.08 mm)

Poles	Width (mm)	Article Designation	Article Number	PU
2	10.76	AKZ700/2-5.08-H-GREEN	50700020274 F	200
3	15.84	AKZ700/3-5.08-H-GREEN	50700030274 F	200
4	20.92	AKZ700/4-5.08-H-GREEN	50700040274 F	200
5	26.00	AKZ700/5-5.08-H-GREEN	50700050274 F	200
6	31.08	AKZ700/6-5.08-H-GREEN	50700060274 E	100
7	36.16	AKZ700/7-5.08-H-GREEN	50700070274 E	100
8	41.24	AKZ700/8-5.08-H-GREEN	50700080274 E	100
9	46.32	AKZ700/9-5.08-H-GREEN	50700090274 E	100
10	51.40	AKZ700/10-5.08-H-GREEN	50700100274 D	50
11	56.48	AKZ700/11-5.08-H-GREEN	50700110274 D	50
12	61.56	AKZ700/12-5.08-H-GREEN	50700120274 D	50

Technical drawing

