

KEMET Part Number: C1206C331KCGACTU
(C1206C331KCGAC7800)



Capacitor, Ceramic, SMD, MLCC, Ultra-Stable, Low Loss, Class I, 330 pF, +/-10% Tol, 500V, COG, 1206



CeramicChipSolutions
© 2013 KEMET Inc.
All rights reserved

Dimensions (mm)		
Symbol	Dimension	Tolerance
L	3.20	+/-0.20
W	1.60	+/-0.20
T	1.20	+/-0.15
B	0.50	+/-0.25

Packaging Specifications	
Package Kind:	T&R
Package Size:	7in
Package Type:	Plastic Tape
Package Quantity:	2500

General Information	
Supplier:	KEMET
Part Type Description:	SMD, MLCC, Ultra-Stable, Low Loss, Class I

Specifications	
Capacitance:	330 pF
Chip Size:	1206
Voltage:	500V
Temperature Coefficient:	COG
Tolerance:	+/-10%
Application:	Standard Chip
Termination Type:	Tin
Marked:	No
Temperature Range:	-55/+125C
Dissipation Factor:	0.1%
Insulation Resistance:	100 GOhm
Dielectric Strength:	750V

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



© 2006-2013 IntelliData.net