Foam Flux and Thinner / Etching Fluids Sodium Persulphate

R3511 = Product group; Product group discount R 35 1_

GIE-TEC Foam Flux and Thinner

Low-Solid

Series: FL, FT

Part Nr.	Part Description
FL154085	Low-Solid Foam Flux 1000ml
FT155086	Flux Thinner for FL154085 1000ml

FL154085 Low Solid Foam Flux

Features

- · Low solid, no-clean foam flux
- · Also suitable for lead-free soldering
- · Leaves no flux residue traces behind
- No PCB cleaning necessary

Note

Foam flux FT154085 should not be mixed with FT154081 or with other foam fluxes.

FT155086 Flux Thinner for FL154085

Features

Adjust flux thinner amount to the thickness of the fluxer FL154085 (foam flux)

Note

You will find suitable fluxing and drying tank in this catalogue at product group T3611.

Terms of Delivery

Minimum order quantity: 1 PKU = 1 piece

Manufacturer: "gle toc-

http://www.gie-tec.de





R3515 = Product group; Product group discount R 35 1_

GIE-TEC Etching Fluids Sodium Persulphate

For Manufacturing PCBs Series: NAP

Application

Sodium persulphate etching fluid for etching Cu PCBs in etching

250g of sodium persulphate is dissolved in 1 liter of water. The etchant turns a blue colour at saturation.

Features

- Neutral smell
- · Slightly soluble in water
- Added solution is transparent · No sludge formation and crystallization
- · Etching procedures easy to monitor
- Easy disposal

Note

 Keep the solution sealed and away from children. In case of contact with skin or eyes, rinse with plenty of water, contact a doctor immediately and take the empty container with you. You will find etching tanks in this catalogue at product group T3311.

Terms of Delivery

Minimum order quantity: 1 PKU = 1 piece

Manufacturer: - 910-100http://www.gie-tec.de

Part Nr.	Part Description
NAP00.6	Sodium Persulphate 600g
NAP01	Sodium Persulphate 1kg



