




**SAFETY ISOLATING TRANSFORMER**


POWER : 0.6VA  
 INPUT VOLTAGE : 230V  
 FREQUENCY : 50/60Hz  
 NOMINAL OUTPUT VOLTAGE : 15V

INHERENTLY SHORT CIRCUIT PROOF TRANSFORMER  
 IPOO  
 UL94V0  
 OPERATING TEMPERATURE : -25°C to 70°C  
 STORAGE TEMPERATURE : -25°C to 85°C  
 INSULATION CLASS (IEC85) : B  
 INHERENT PROTECTION

STANDARDS :  
 UL506 (File E111078)  
 CSA 22-2 (File E111078)  
 UL1585 (File E240724)  
 VDE (File Ref:1398300)  
 EN60950 (File Ref:1398300)  
 EN61558-1 (File Ref:1398300)  
 EN61558-2-6 (File Ref:1398300)  
 CE



<p>44016          230V 50/60Hz (1-5)          15V 0.6VA          ta 70/B          CE</p>	<p>EN 60950          Class II not wet          Class III wet</p>	<p>N°10</p>
--	--	-------------



Finition:		Tolérance générale:	
Finition:		General tolerance:	
Ech: 1:1	Matière:		
	Material:		
Dessiné par: ROUSSEL.Ch	Date: 10/05/2004	Visa:	J.P.M.

D					
C					
B					
A					
Rev	Date	Modification	Dessiné	Visa	

**DATA SHEET 44016**  
**EI 30x5**

	22 Allée du Clos des Charmes Z.A. Les Portes de la Forêt 77090 COLLEGIEN Tel : 01-60-37-55-55 Fax : 01-60-17-12-00	<p style="font-size: 2em;"><b>DS44016</b></p>
--	--	---